DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS D206-540 REV. J REF CANADIAN STC: SH94-5 REF FAA STC: SR00386NY

REF GERMAN STC: LBA RC 1124

PURPOSE

THIS DART SERVICE INSTRUCTION PROVIDES PARTS AND INSTRUCTIONS FOR MODIFYING A D206-540-013 HELI-UTILITY-BASKET FOR INSTALLATION OF SCANNING EQUIPMENT.

MODIFICATION PROCEDURE:

- 1) DISASSEMBLE BASKET AND RETAIN HARDWARE.
- 2) LOCATE THE D4317-1 VIEWING PLATE AND D4317-3 WIRING PLATE AND TRIM EXPANDED METAL AS SHOWN IN FIGURE 1 AND SECTIONS A-A & B-B. REMOVE FINISH ON EXPANDED METAL LOCALLY AND TIG WELD (TACK WELD) D4317-1 AND D4317-3 TO THE EXPANDED METAL, PER MIL-STD-2219/AMS-STD-2219 CLASS 'C' USING ER308L OR ER316L FILLER ROD.
- 3) LOCATE THE D4317-5 GPS PLATE AND TRIM EXPANDED METAL AS SHOWN IN SECTION C-C. REMOVE FINISH ON THE BASKET LID TUBULAR STRUCTURE AND EXPANDED METAL LOCALLY. TIG WELD (FILLET & TACK WELD) D4317-5 TO THE TUBULAR STRUCTURE AND EXPANDED METAL AS SHOWN IN FIGURE 1, PER MIL-STD-2219/AMS-STD-2219 CLASS 'C' USING ER308L OR ER316L FILLER ROD.
- 4) LOCATE D4317-041/-043 AS SHOWN IN SECTION C-C. REMOVE FINISH ON THE BASKET LID TUBES LOCALLY AND TIG WELD THE D4137-041/-043 COVER PANEL RETAINERS IN PLACE PER MIL-STD-2219/AMS-STD-2219 CLASS 'C' USING ER308L OR ER316L FILLER ROD.
- 5) LOCATE QTY (4) D4136-041 TUBE ASSEMBLIES AS SHOWN IN SECTION D-D. REMOVE FINISH ON THE BASKET BASE HOOPS LOCALLY AND TIG WELD THE D4136-041 TUBE ASSEMBLIES IN PLACE PER MIL-STD-2219/AMS-STD-2219 CLASS 'C' USING ER308L OR ER316L FILLER ROD.
- 6) TOUCH UP POWDER COAT OF AFFECTED AREAS ON BOTH LID AND BASE WITH WHITE POWDER COAT (4.3.5.2) PER DART QSI 005 4.3 OR PRIME/PAINT PER AIRCRAFT MAINTENANCE MANUAL.
- 7) RE-ASSEMBLE BASKET PER D206-540 REV J. REPLACE ANY WORN HARDWARE AS NECESSARY.

WEIGHT CHANGE:

THIS MODIFICATION ADDS 4.5 LBS TO THE WEIGHT OF THE BASKET WHICH REDUCES THE CARGO CARRYING CAPACITY OF THE BASKET BY 4.5 LBS.

NOTE:

IF A BASKET MODIFIED PER DSI 9542 IS GOING TO BE USED TO CARRY LOOSE CARGO THE CUTOUTS IN THE EXPANDED METAL FOR D4317-1 & D4317-3 MUST BE COVERED WITH BLANKING PLATES.

DATE

11.02.15

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-0-01

APPROVED #

BY: D. SHEPHERD (DE # 02)

DATE: 11.02.16
CERT. NO.: SH94-5
ISSUE NO.: 4

A	NEW ISS	EW ISSUE			11.02.15
REV.			DESCRIPTION BY DATE		DATE
DESIGN		AJS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWN		AJS			
CHECKE	ED ·	11	DRAWING NO.		REV. A
MFG. AP	PPR.	M.	DSI 9542	S	SHEET 1 OF 4
APPROVED		4	TITLE		SCALE
DE APPR.			BASKET MODIFICATION		NTS

COPYRIGHT © 2011 BY DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.





